


TONARA

RECESSED / PLASTERBOARD
OPAL + MICROPRISMA
IP43



LED		ECG	IP43	ECG DALI	ECG 1-10V	EMERGENCY	5 years warranty	60,000 hrs L80/B10 Ta=25°C	220-240V 50-60Hz		CE
-----	--	-----	------	----------	-----------	-----------	------------------	----------------------------------	---------------------	--	----

on request


TONARA

Recessed / Plasterboard

LIGHT OUTPUT	up to 5500 lm
EFFICIENCY	up to 108 lm/W
WIRING	ECG, on request: DALI, 1-10V On request: Emergency kit (1h, 3h)
CCT	3000 - 4000K
CRI	≥ 80 Ra
MATERIALS	
> Housing & Frame	Sheet steel
> Diffuser	Opal PMMA Mat Pattern + Microprisma PMMA
LIGHT DISTRIBUTION	Direct
SURFACE FINISH	White color (RAL9003); other colors on request
ACCESSORIES	Mounting brackets for Plasterboard ceiling Opening frame with special plate



drawing



Net lumen output	CCT	Power	Dimensions	Weight	Purchase code
(lm)	(K)	(W)	(mm)	(kg)	
3800	3000	37	595x595x100	6.00	TONARA.595.37.3800.3K.43
4000	4000	37	595x595x100	6.00	TONARA.595.37.4000.4K.43
5100	3000	51	595x595x100	6.00	TONARA.595.51.5100.3K.43
5300	4000	51	595x595x100	6.00	TONARA.595.51.5300.4K.43